




## The flame-retardant rubber mat with the AGR seal of approval.

- o The ERGOLASTEC Fire is flame-retardant in **accordance with EN13501-1/floor covering test**, and therefore also suitable for use in public buildings.
- o The tested rubber mat can be used at **grinding and welding workstations.\*\***
- o The flame-retardant rubber mat has the **fire protection class Bfl-S1.\*\***
- o Heat resistance to **short-term sparks and welding beads.**




flame-resistant



Surface	Size	Fire protection class	Material	Hardness	Weight	Colour
FIRE Dry	1350 x 1000 x 16 mm*	Bfl-s1**	SBR***	55 Shore A	19 ± 1 kg	
FIRE Wet	1350 x 1000 x 20 mm*	Bfl-s1**	SBR***	55 Shore A	19,5 ± 1 kg	
FIRE Diamond	1350 x 1000 x 19 mm*	Bfl-s1**	SBR***	55 Shore A	19,5 ± 1 kg	

## Oberflächen- und Rückseitengeometrien



Flame-retardant mat Bfl-s1



Dry working conditions



Humid working conditions



Slippery working conditions

\* Tolerances according to DIN ISO 3302 - 1 M4; \*\* According to EN 13501 resistant to short-term flying sparks and welding beads

\*\*\* Slight discolouration may occur on light floors

